

## SPECIFICATIONS

Model	HT1600UV- Gen6
Printhead	Ricoh Gen6
Quantity of printheads	2-8 pcs(Double rows)
Resolution	1200*1200dpi
Draft	46.5 m <sup>2</sup> /h
Print speed Production	40 m <sup>2</sup> /h
Quality	29 m <sup>2</sup> /h
Max print width	1.6m
Max media thickness	50mm
Media type	Rigid and flexible flat materials
Ink	Environmental friendly UV/LED curable ink(VOC free)
Ink color	C, M, Y, K, Lc, Lm, W (varnish is optional)
Machine size(L*W*H)	4.32*1.26*1.37 m
Machine net weight	800KG
Machine gross weight	1210KG
Power consumption	5.3 KW(23A)
Power supply	230VAC. 50Hz L/N/PE
RIP support	Caldera
UV Curing	LED
Interface	High Speed PCIE
Environment	Seperated workroom in good cleaning and ventilated condition, avoid direct sunlight Temperature: 18° C – 30° C(64°F-86°F) Constant Humidity: 30%-70%

# HandTOP

## HT 1600 UV Hybrid Printer



**Create value for customers; be a world-leading manufacturer of smart digital printing equipment.**

- Diversified product configuration and application solution can match the different demand in advertising, decorating, glass and other industries.
- Reliable stability combines the outstanding printing quality and speed performance.
- Top-level R&D team ensures prompt optimization and upgrade for new products and keep advanced technology in digital printing field.
- Strong worldwide after-sales service team quickly shoots your problem.
- High cost-value product brings you more business.

©Above information for reference only and subject to change without notice. Shenzhen Handtop Tech Co.,Ltd all rights reserved.

# HandTOP