

SPECIFICATIONS

| Model | HT1600UV | | HT2500UV | | HT3200UV | | |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------|
| Printhead | Ricoh Gen5 | Ricoh Gen6 | Ricoh Gen5 | Ricoh Gen6 | Ricoh Gen5 | Ricoh Gen6 | |
| Quantity of printheads | 2 - 4pcs (Single row) | 4 pcs (Double rows) | 4 - 8 pcs (Double rows) | 4 - 8 pcs (Double rows) | 4 - 8 pcs (Double rows) | 4 - 8 pcs (Double rows) | |
| Resolution | 1200 * 1200 dpi | | | | | | |
| Print speed | Draft | 22 m ² /h | 52 m ² /h | 46 m ² /h | 65 m ² /h | 51 m ² /h | 74 m ² /h |
| | Production | 14 m ² /h | 36 m ² /h | 33 m ² /h | 44 m ² /h | 36 m ² /h | 55 m ² /h |
| | Quality | 10 m ² /h | 28 m ² /h | 23 m ² /h | 30 m ² /h | 24 m ² /h | 40 m ² /h |
| Print mode | Unidirectional & Bidirectional | | | | | | |
| Max width | 1.6 m | | 2.5 m | | 3.2 m | | |
| Max media thickness | 50 mm | | | | | | |
| Media type | Rigid and flexible flat materials | | | | | | |
| Ink | Environmental friendly UV/LED curable ink (VOC free) | | | | | | |
| Ink color | C, M, Y, K, Lc, Lm, W (varnish is optional when there is no Lc and Lm) | | C, M, Y, K, Lc, Lm, W | | | | |
| Image format | Adobe Postscript Level3, PDF, JPEG, TIFF, EPS, AI | | | | | | |
| Machine size(L*W*H) | 4.15 * 1.19 * 1.33 m | | 5.49 * 1.15 * 1.38 m | | 6.19 * 1.59 * 1.56 m | | |
| Machine net weight | 760 KG | | 1280 KG | | 2260 KG | | |
| Machine gross weight | 1170 KG | | 1875 KG | | 3130 KG | | |
| Power consumption | 5.3 KW (27 A) | | 8.0 KW (20 A) | | 9.0 KW (20 A) | | |
| Power supply | 230 VAC. 50 Hz L/N/PE | | 400 VAC. 50 Hz 3P/N/PE | | | | |
| Certification | CE / FCC | | | | | | |
| RIP support | Caldera, Onyx | | | | | | |
| UV curing | Water-cooled UV_LED Lamp | | | | | | |
| Interface | High Speed PCIE | | | | | | |
| Environment | Seperated workroom in good cleaning and ventilated condition, avoid direct sunlight Temperature: 18 – 30° C (64 - 86°F) Constant Humidity: 30 - 70% | | | | | | |

©Above information for reference only and subject to change without notice. Shenzhen Handtop Tech Co.,Ltd all rights reserved.

HandTOP

HT 2500 UV Hybrid Printer



Create value for customers; be a world-leading manufacturer of smart digital printing equipment.

- Diversified product configuration and application solution can match the different demand in advertising, decorating, glass and other industries.
- Reliable stability combines the outstanding printing quality and speed performance.
- Top-level R&D team ensures prompt optimization and upgrade for new products and keep advanced technology in digital printing field.
- Strong worldwide after-sales service team quickly shoots your problem.
- High cost-value product brings you more business.