

HT 2500 UV Gen 6

Specifications

Model	HT 2500 UV Gen 6	
Printhead	2 - 8 Ricoh Gen6	
Resolution	600 x 1800 DPI	
Capacity	Draft Mode	60 m ² /h
	Production Mode	45 m ² /h
	Quality Mode	31 m ² /h
Max. Print Width	2.5 x 1.22 m	
Material Thickness	100 mm	
Applications	A wide variety of application in terms of acrylic, PVC, wood, glass, ceramic tile etc.	
Ink	eco-friendly UV curing ink (VOC free)	
Color	C, M, Y, K, Lc, Lm, V, W	
Dimension (L x W x H)	4.67 x 2.51 x 1.38 m	
Net Weight	1150 Kg	
Gross Weight	1745 Kg	
Power Supply	400VAC.50Hz 3P/N/PE; UV LED light 230VAC.50Hz L/N/PE	
Power Consumption	7KW (18A) , LED light 2.5KW (11A)	
RIP Software	Caldera	
UV Curing System	LED	
Interface	Hi-Speed PCIE	
Operating Environment	Temperature: 18°C~30°C (64°F~86°F)	
	Relative Humidity: 30%~70% (non-condensing)	

©Above information for reference only and subject to change without notice.

HandTOP

HT 2500 UV Gen 6



UV Hybrid Printer

- World-Class industrial design & excellent image data processing technology
- Wide variety of applications in broad field including brand lightbox advertisement in subway, airport & shopping mall and ceiling soft film project
- A top-level R&D team with 20 years of industry experience & 37 patents
- Obtained ISO:9001 International Quality System Certification & EU CE Certification
- Worldwide customer support , 24 x 7 technical support and service



HandTOP